

## ECN020-32P

## Through hole slip ring

This is a 20mm through hole, 32 wires of power slip ring, the whole body use aluminium alloy material, the contact materials is gold to gold, it's with high-performance and longer life service. It's also can integrate various of signal such as Ethernet, Canbus, RS485/232/422 etc. We are professional on shielding technology, anti-interference for line to line. We not only provide products, but also provide solutions! According to different requirements of customers for electrical, signal, data, gas and liquid rotary connection, as well as different power parameter requirements, we provide the best solution to save your time and cost.

### Advantages


- ◆ With gold contacts
- ◆ Stable power performance
- ◆ Shaft-mounted
- ◆ Compact size

### Applications

- ◆ Rotary table
- ◆ Cable reels
- ◆ Packaging machine
- ◆ Wrapping machines

### Optional

- ◆ Through hole size
- ◆ Current & ring numbers
- ◆ Signal type
- ◆ IP protection grade

ECN020-32P	Specification	Picture
Circuits & Current	6*10A, 22*5A, 4*2A	
Voltage	0-410VAC/VDC	
Dielectric strength	≥1000V@50Hz	
Insulation resistance	≥500MΩ@500VDC	
Operating speed	0-200 rpm	
Contact material	Gold-gold	
Housing material	Aluminium alloy	
IP protection grade	IP54	
Through hole size	20 mm	
Working temperature	-20° C ~ +60° C	
Cable length	1700mm / 2200mm	

### Outline Drawing

